


DKD&) \$

- : Perkins 1506A-E88TAG2
- : 50
- : IP23 H H
- :
- 24V 24V
-
-
-
-
-
-

ATS

		PWP250
KW/KVA		180/225
KW/KVA		198/248
(HZ)		50
(VAC)		400
	L/H	41.2
		± 5%
		± 1%
	/100%	25%
	/	-20%
	/100% (S)	6
	/ (S)	6
	/100%	12%
	/	-10%
	/100% (S)	5



Dyf_] bg

- PERKINS
-
-
-
-
-
-
-

NOx < 2000mg/m

4000 24

/ PERKINS

KW	205	228
BHP	275	306
r/min	1500	
	6	
	L	

x 112x149mm
8.8L
16.1 1

L	29.6
(L)	41
L/S	240
L/S	574
	467

()			
g/kwh	NA	205.4	194.4 197

ê

25°C(77°F)	ISO 3046	—	110m(361ft)	100kPa (29.53inHg)
	30%	NO.2	ASTM D2	

178=&+(>%

A 4 4 4

4				A4
				A4
				A4
				m ³ /s

#

- Comap
-
-
-
-

SMARTGEN DEIF



/

RS-232 Modbus

" "

#

	* * mm	(KG)
	2850*1100*1500	2500
	3700*1270*2150	3280

